

## Homework Assignment #4

### Note

This assignment is due 2:10PM Tuesday, March 29, 2016. Please write or type your answers on A4 (or similar size) paper. Drop your homework by the due time in Yih-Kuen Tsay's mail box on the first floor of Management College Building II. Late submission will be penalized by 20% for each working day overdue. You may discuss the problems with others, but copying answers is strictly forbidden.

### Problems

There are five problems in this assignment, each accounting for 20 points. (Note: problems marked with "(X.XX)" are taken from [Manber 1989] with probable adaptation.)

1. (5.7) Write a program (or modify the code discussed in class) to recover the solution to a knapsack problem using the *belong* flag. You should make your solution as efficient as possible.
2. (5.8) In algorithm *Knapsack*, we first checked whether the  $i$ th item is unnecessary (by checking  $P[i - 1, j]$ ). If there is a solution with the  $i - 1$  items, we take this solution. We can also make the opposite choice, which is to take the solution with the  $i$ th item if it exists (i.e., check  $P[i - 1, j - k_i]$  first). Which version do you think will have a better performance? Redraw Fig. 5.11 (see notes/slides) to reflect this choice.
3. (5.11) Suppose that there are two different (maybe proposed) skylines: One is projected on a screen with a blue color, and the other is superimposed on the first one with a red color. Design an efficient algorithm to compute the shape that will be colored purple. In other words, compute the intersection of two skylines. Please present your algorithm in suitable pseudocode.
4. (5.17) The Knapsack Problem that we discussed in class is defined as follows: Given a set  $S$  of  $n$  items, where the  $i$ th item has an integer size  $S[i]$ , and an integer  $K$ , find a subset of the items whose sizes sum to exactly  $K$  or determine that no such subset exists.  
We have described in class an algorithm to solve the problem. Modify the algorithm to solve a variation of the knapsack problem where each item has an *unlimited* supply. In your algorithm, please change the type of  $P[i, k].belong$  into integer and use it to record the number of copies of item  $i$  needed.
5. (5.20) Let  $x_1, x_2, \dots, x_n$  be a set of integers, and let  $S = \sum_{i=1}^n x_i$ . Design an algorithm to partition the set into two subsets of equal sum, or determine that it is impossible to do so. The algorithm should run in time  $O(nS)$ .